



Department of Transportation  
**Federal Aviation Administration**  
Aircraft Certification Service  
Washington, D.C.

**TSO-C115d**

Effective  
Date: {mm/dd/yy}

# Technical Standard Order

---

**Subject: REQUIRED NAVIGATION PERFORMANCE (RNP)  
EQUIPMENT USING MULTI-SENSOR INPUTS**

**1. PURPOSE.** This technical standard order (TSO) is for manufacturers applying for a TSO authorization (TSOA) or letter of design approval (LODA). In it, we (the Federal Aviation Administration, (FAA)) tell you what minimum performance standards (MPS) your RNP equipment must first meet for approval and identification with the applicable TSO marking.

**2. APPLICABILITY.** This TSO affects new applications submitted after its effective date.

**a.** TSO-C115c will remain effective until *<18 months after the date of publication>*. After this date, we will no longer accept applications for TSO-C115c.

**b.** Flight management systems, and other navigation computer equipment, approved under a previous TSO-C115 TSOA may still be manufactured under the provisions of its original approval.

**c.** This TSO supports performance-based operations using RNP values from RNP 0.3 through RNP 4.0.

**d.** This TSO does not address RNP operations with authorization required (RNP AR), localizer performance without vertical guidance/localizer performance with vertical guidance (LP/LPV), or ground-based augmentation system landing system (GLS) approach operations. See applicable TSOs and advisory circulars for information on these operations.

**3. REQUIREMENTS.** New models of RNP equipment, identified and manufactured on or after the effective date of this TSO must meet the MPS qualification and documentation requirements for Class A or Class B specified in Sections 2.1 and 2.2 of RTCA Inc. Document No. RTCA/DO-283B, *Minimum Operational Performance*

*Standards for Required Navigation Performance for Area Navigation*, December 15, 2015, as modified by appendix 1 of this TSO. Requirements applicable to Class A and Class B equipment are specified in RTCA/DO-283B, Table 2-13.

**a. Functionality.** This TSO's standards apply to RNP equipment intended to provide a navigation function outputting deviation commands keyed to a desired flight path. The applicant shall specify whether they are seeking Class A or Class B recognition for their RNP equipment. Pilots or autopilots will use the deviations output by the RNP equipment to guide the aircraft.

**b. Failure Condition Classifications.**

**(1) RNP 0.3 through 4.0**

**(a)** Failure of the function defined in paragraph **3.a** resulting in misleading lateral or vertical guidance is a major failure condition.

**(b)** Loss of the function defined in paragraph **3.a** is a major failure condition for lateral guidance and a minor failure condition for vertical guidance provided by barometric-vertical navigation (baro-VNAV) equipment.

**(c)** Loss of the function defined in paragraph **3.a** is a major failure condition for lateral guidance and a major failure condition for vertical guidance provided by satellite-based augmentation system (SBAS) equipment.

**Note 1:** Both baro-VNAV and SBAS are eligible to provide vertical guidance on an RNP approach. This is lateral navigation (LNAV)/VNAV, not LPV.

**Note 2:** Loss of function for vertical guidance is a major failure condition when using SBAS equipment because lateral and vertical guidance are not independent (see the latest revision of AC 20-138 paragraph 12-2.a).

**(2) Design the RNP equipment to the appropriate failure condition classifications consistent with the sensor used.**

**c. Functional Qualification.** Demonstrate the required functional performance under the test conditions specified in Section 2.4 of RTCA Inc. Document No. RTCA/DO-283B, *Minimum Operational Performance Standards for Required Navigation Performance for Area Navigation*, dated December 15, 2015.

**d. Environmental Qualification.** Demonstrate the required performance under the test conditions specified in Section 2.3 of RTCA Inc. Document No. RTCA/DO-283B, *Minimum Operational Performance Standards for Required Navigation Performance for Area Navigation*, dated December 15, 2015, using standard environmental conditions and

test procedures appropriate for airborne equipment. You may use a different standard environmental condition and test procedure than RTCA/DO-160D, Change 3, provided the standard is appropriate for the RNP equipment.

**Note:** The use of RTCA/DO-160D (with Changes 1 and 2 only, without Change 3 incorporated) or earlier versions is generally not considered appropriate and will require substantiation via the deviation process as discussed in paragraph 3.g of this TSO.

**e. Software Qualification.** If the article includes software, develop the software according to RTCA, Inc. Document RTCA/DO-178C, *Software Considerations in Airborne Systems and Equipment Certification*, dated December 13, 2011, including referenced supplements as applicable, to at least the software level consistent with the failure condition classification defined in paragraph **3.b** of this TSO. You may also develop the software according to RTCA, Inc. Document RTCA/DO-178B, dated December 1, 1992, if you follow the guidance in AC 20-115C, *Airborne Software Assurance*, dated July 19, 2013.

**f. Electronic Hardware Qualification.** If the article includes complex custom airborne electronic hardware, develop the component according to RTCA, Inc. Document RTCA/DO-254, *Design Assurance Guidance for Airborne Electronic Hardware*, to at least the design assurance level consistent with the failure condition classification defined in paragraph **3.b** of this TSO. For custom airborne electronic hardware determined to be simple, RTCA/DO-254, paragraph 1.6 applies.

**g. Deviations.** We have provisions for using alternate or equivalent means of compliance to the criteria in the MPS of this TSO. If you invoke these provisions, you must show that your equipment maintains an equivalent level of safety. Apply for a deviation pursuant to Title 14 of the Code of Federal Regulations (14 CFR) § 21.618.

#### **4. MARKING.**

**a.** Mark at least one major component of the RNP equipment permanently and legibly with all the information in 14 CFR § 45.15(b)

**b.** Also, mark the following permanently and legibly, with at least the manufacturer's name, subassembly part number, and the TSO number:

(1) Each component that is easily removable (without hand tools); and,

(2) Each subassembly of the article that you determined may be interchangeable.

**c.** If the article includes software and/or airborne electronic hardware, then the article part numbering scheme must identify the software and airborne electronic

hardware configuration. The part numbering scheme can use separate, unique part numbers for software, hardware, and airborne electronic hardware.

**d.** You may use electronic part marking to identify software or airborne electronic hardware components by embedding the identification within the hardware component itself (using software) rather than marking it on the equipment nameplate. If electronic marking is used, it must be readily accessible without the use of special tools or equipment.

**5. APPLICATION DATA REQUIREMENTS.** You must give the FAA aircraft certification office (ACO) manager responsible for your facility a statement of conformance, as specified in 14 CFR § 21.603(a)(1) and one copy each of the following technical data to support your design and production approval. LODA applicants must submit the same data (excluding paragraph **5.g**) through their civil aviation authority.

**a.** A Manual(s) containing the following:

**(1)** Operating instructions and article limitations sufficient to describe the equipment's operational capability.

**(2)** Identify the RNP equipment class; Class A or Class B.

**(3)** Instructions for updates to ensure continued airworthiness (e.g., magnetic variation tables).

**(4)** Describe in detail any deviations.

**(5)** Installation procedures and limitations sufficient to ensure that the RNP equipment, when installed according to the installation or operational procedures, still meets this TSO's requirements. Limitations must identify any unique aspects of the installation. The limitations must include a note with the following statement:

“This article meets the minimum performance and quality control standards required by a technical standard order (TSO). Installation of this article requires separate approval.”

**(6)** For each unique configuration of software and airborne electronic hardware, reference the following:

**(a)** Software part number including revision and design assurance level;

**(b)** Airborne electronic hardware part number including revision and design assurance level; and,

**(c)** Functional description.

(7) A summary of the test conditions used for environmental qualifications for each component of the article. For example, a form as described in RTCA/DO-160G, *Environmental Conditions and Test Procedures for Airborne Equipment*, Appendix A.

(8) Schematic drawings, wiring diagrams, and any other documentation necessary for installation of the RNP equipment using multisensory inputs.

(9) List of replaceable components, by part number, that makes up the RNP equipment. Include vendor part number cross-references, when applicable.

b. Provide instructions covering periodic maintenance, calibration, and repair, to ensure the RNP equipment continues to meet the TSO approved design. Include recommended inspection intervals and updates for continued airworthiness (e.g. magnetic variation tables), as appropriate.

c. If the article includes software: a plan for software aspects of certification (PSAC), software configuration index, and software accomplishment summary.

d. If the article includes simple or complex custom airborne electronic hardware: a plan for hardware aspects of certification (PHAC), hardware verification plan, top-level drawing, and hardware accomplishment summary (or similar document, as applicable).

e. A drawing depicting how the article will be marked with the information required by paragraph 4 of this TSO.

f. Identify functionality or performance contained in the article not evaluated under paragraph 3 of this TSO (that is, non-TSO functions). Non-TSO functions are accepted in parallel with the TSO authorization. For those non-TSO functions to be accepted, you must declare these functions and include the following information with your TSO application:

(1) Description of the non-TSO function(s), such as performance specifications, failure condition classifications, software, hardware, and environmental qualification levels. Include a statement confirming that the non-TSO function(s) do not interfere with the article's compliance with the requirements of paragraph 3.

(2) Installation procedures and limitations sufficient to ensure that the non-TSO function(s) meets the declared functions and performance specification(s) described in paragraph 5.f.(1).

(3) Instructions for continued performance applicable to the non-TSO function(s) described in paragraph 5.f.(1).

(4) Interface requirements and applicable installation test procedures to ensure compliance with the performance data defined in paragraph 5.f.(1).

(5) Test plans, analysis and results, as appropriate, to verify that performance of the hosting TSO article is not affected by the non-TSO function(s).

(6) Test plans, analysis and results, as appropriate, to verify the function and performance of the non-TSO function(s) as described in paragraph 5.f.(1).

g. The quality system description required by 14 CFR § 21.608, including functional test specifications. The quality system should ensure that you will detect any change to the approved design that could adversely affect compliance with the TSO MPS, and reject the article accordingly. (Not required for LODA applicants.)

h. Material and process specifications list.

i. List of all drawings and processes (including revision level) that define the article's design.

j. Manufacturer's TSO qualification report showing results of testing accomplished according to paragraph 3.c of this TSO.

**6. MANUFACTURER DATA REQUIREMENTS.** Besides the data given directly to the responsible ACO, have the following technical data available for review by the responsible ACO:

a. Functional qualification specifications for qualifying each production article to ensure compliance with this TSO.

b. Article calibration procedures.

c. Schematic drawings.

d. Wiring diagrams.

e. Material and process specifications.

f. The results of the environmental qualification tests conducted according to paragraph 3.d of this TSO.

g. If the article includes software, the appropriate documentation defined in RTCA/DO-178B or RTCA/DO-178C specified in paragraph 3.e of this TSO, including all data supporting the applicable objectives in RTCA/DO-178B Annex A, *Process Objectives and Outputs by Software Level*.

h. If the article includes complex custom airborne electronic hardware, the appropriate hardware life cycle data in combination with design assurance level, as defined in RTCA/DO-254, Appendix A, Table A-1. For simple custom airborne electronic hardware, the following data: test cases or procedures, test results, test

coverage analysis, tool assessment and qualification data, and configuration management records, including problem reports.

i. If the article contains non-TSO function(s), you must also make available items **6.a** through **6.h** as they pertain to the non-TSO function(s).

## **7. FURNISHED DATA REQUIREMENTS.**

a. If furnishing one or more articles manufactured under this TSO to one entity (such as an operator or repair station), provide one copy or on-line access to the data in paragraphs **5.a** and **5.b** of this TSO. Add any other data needed for the proper installation, certification, use, or for continued compliance with the TSO, of the RNP equipment.

b. If the article contains declared non-TSO function(s), include one copy of the data in paragraphs **5.f.(1)** through **5.f.(4)**.

## **8. HOW TO GET REFERENCED DOCUMENTS.**

a. Order RTCA documents from RTCA Inc., 1150 18th Street NW, Suite 910, Washington, D.C. 20036. Telephone (202) 833-9339, fax (202) 833-9434. You can also order copies online at [www.rtca.org](http://www.rtca.org).

b. Order copies of 14 CFR parts 21 and 45 from the Superintendent of Documents, Government Printing Office, P.O. Box 979050, St. Louis, MO 63197. Telephone (202) 512-1800, fax (202) 512-2250. You can also order copies online at [www.gpo.gov](http://www.gpo.gov).

c. You can find a current list of technical standard orders and advisory circulars on the FAA Internet website Regulatory and Guidance Library at <http://rgl.faa.gov/>. You will also find the TSO Index of Articles at the same site.

Susan J. M. Cabler  
Acting Manager, Design, Manufacturing, &  
Airworthiness Division  
Aircraft Certification Service

## APPENDIX 1. EXCEPTIONS TO RTCA/DO-283B REQUIREMENTS

### Scope.

This appendix describes modifications to the requirements found in RTCA/DO-283B the RNP equipment shall meet for compliance with this TSO.

#### 2.2.1.2.1 Leg Types.

Add the following required leg types to Table 2-1:

FM	Fix to Manual Termination
VA	Heading to Altitude Leg
VI	Heading to Intercept
VM	Heading to Manual Termination

Add the following requirement and note after the sentence “Refer to Appendix D for additional details for each of the leg types”:

The equipment shall have the ability to use an IF that is a fly-by waypoint, fly-over waypoint, or the initial fix defining an RF leg segment. Additionally, the equipment shall have the ability to proceed “direct to” an IF.

*Note: This requirement is needed to support RNP departure procedures, particularly those with an RF leg as the first leg segment, where the IF defines the beginning of the RF leg. With LNAV available immediately after takeoff, the equipment should provide guidance direct to the IF and sequence the next leg; particularly when the IF is the initial fix of an RF leg).*

#### 2.2.1.2.2 Flight Planning.


Insert a new paragraph and note below between the last paragraph and next to last paragraph:

The equipment shall have the ability to use a single waypoint supporting multiple RNP terminal procedures (SID, DP, STAR) and multiple approach procedures using different tracks. When a single waypoint supports an arrival and an RNP instrument approach using different tracks, the equipment shall continue following the arrival procedure to the procedure’s termination fix and shall not automatically sequence onto the RNP approach procedure using that same waypoint.

*Note: Some waypoints may serve as: a transition fix for an instrument approach; an initial approach fix (IAF) for an instrument approach; the first fix in a terminal arrival*



procedure; and an intermediate waypoint on a terminal RNP procedure (SID, DP or STAR) (see Figure 1 below). This requirement ensures the equipment completes RNP procedures as assigned by ATC, and loaded by the flight crew into the active flight plan from the onboard navigation database.



**Figure 1. Single Waypoint Serving Multiple RNP Procedures.**

Add the following requirement and note after the last paragraph in the section 2.2.1.2.2:

The equipment shall not permit the flight crew to select a procedure or route, either manually or automatically, that is not supported by the equipment. For example, a procedure is not supported if it incorporates advanced RNP functions and the equipment does not provide those advanced RNP functions.

*Note: Procedures (approaches, arrivals, departures, routes) are defined by a series of waypoints and leg types.*

#### **2.2.1.4.14 Electronic Map Display.**

Add the following as note 2:

*Note 2: Manufacturers should use RTCA/DO-257A with RTCA/DO-283A, appendix K until RTCA/DO-257B is published.*

#### **2.2.2.2.6.1 Descent Path Construction.**

Add the following requirement and note to the list of general requirements:

6. The RNP equipment shall always use the procedure-defined flight path angle to define the final approach segment of an RNP instrument approach procedure offering vertical guidance (RNP procedures offering LNAV/VNAV minima).

*Note: Some RNP instrument approach procedures define the final approach fix with an ‘AT’ altitude constraint (“hard” altitude”) and the intent of this requirement is to use the published FPA, the designated end of the runway (DER) and the threshold crossing height for vertical path construction. The equipment should **not** generate a geometric, point-to-point vertical path between two ‘AT’ constraints on a final approach segment.*

#### 2.4.3.1 Test Scenario(s).

Add the following leg types to the list in paragraph (a):


FM, VA, VI, VM.

#### Appendix D.

Add the following leg type definitions to Appendix D:

##### D.10 Fix to Manual Termination (FM).


An FM leg defines a specified track over the ground from a database fix until a manual termination of the leg.



**Figure D-6: Fix to Manual Termination (FM) Leg**

##### D.11 Heading to Altitude (VA).


A VA leg defines a specified heading to a specific altitude termination at an unspecified position. No correction is made for wind.



**Figure D-7: Heading to Altitude (VA) Leg**

**D.12 Heading to Intercept (VI).**


A VI leg defines a specified heading to intercept a subsequent leg at an unspecified position. No correction is made for wind.



**Figure D-8: Heading to Intercept (VI) Leg**

**D.13 Heading to Manual Termination (VM).**

A VM leg defines a specified heading until a manual termination of the leg. No correction is made for wind.



**Figure D-9: Heading to Manual Termination (VM) Leg**